HOODS

AVANTE-SEF

HIGH EFFICIENCY EXTRACT CANOPY WITH MAKEUP AIR AND INDUCTION NOZZLES



Avante-SEF canopy is an extract canopy with makeup air plenum equipped with front and side induction nozzles to contain and extract fumes and heat within the hood area, thereby improving the extract efficiency and working conditions.

The makeup air to the hood is from the front perforated plenum and treated makeup air is introduced at low velocity to the cooking space to improve the comfort in the cooking area.

The makeup air is integrated into the hood structure, and the plenum is insulated.

APPLICATION

- Avante-SEF is designed with highefficiency filtration capabilities and superior fire safety
- Avante-SEF is well-suited to all types of commercial and professional kitchens
- Equipped with a space-saving integrated makeup air system, featuring a double skin design that simplifies the balancing of kitchen air flows and eliminates the need for extra makeup terminals, leading to a project cost reduction

CUSTOMIZATION

- Wall mounted
- Island mounted
- 600mm height, 1350mm depth (min), length varies according to layout requirements

MAINTENANCE

 Dripping grease is arrested with vane and collected in an easily accessible grease tray

OPTIONS

- LED dimmable spotlights
- Service Distribution Unit
- Factory-installed hood Fire Suppression System
- Factory-installed hood Demand Control Ventilation System
- Hood cladding / powder coating



HOODS

AVANTE-SEF

HIGH EFFICIENCY EXTRACT CANOPY
WITH MAKEUP AIR AND INDUCTION NOZZLES


FILTRATION

- Heavy duty Stainless Steel welded construction
- Filtration efficiency of 95% for 6-8 microns
- UL listed
- DMT certified for filtration efficiency
- Meets NFPA #96 requirements



CONSTRUCTION

- Fully made of 1.2mm SS AISI 304 brush finish
- Double skin with front perforated supply section equipped with induction fan
- Welded construction
- Full-length induction nozzle slot on the front and sides to improve the extraction efficiency
- Sliding balancing dampers
- Extract air flow calculations as per DW 172
- Modular construction



TECHNICAL SPECIFICATIONS	
MATERIAL:	SS AISI 304 brush finish
	Thickness: 1.2mm
MAKEUP AIR:	 Front perforated SS AISI 304 brush finish insulated supply plenum
POWER SUPPLY:	• 120/220 - 240 V
	• 50 - 60 Hz
LIGHTING:	Fluorescent or LED lights
	Rated IP65
	 500 lux on the working surface
	 Low consumption
	Heat & vapor resistance
	Long-lasting
DIMENSIONS:	• 600 mm (Height)
	• 1350 mm (Depth min)
	Length: customized

GREASE FILTERS CERTIFICATIONS:








www.avanteuae.com


HOODS


AVANTE-SEF

HIGH EFFICIENCY EXTRACT CANOPY WITH MAKEUP AIR AND INDUCTION NOZZLES

TECHNICAL DRAWINGS







Wall mounted Hood

